

DRILLING FLUIDS ADDITIVES



NAME	DESCRIPTION	CHEMICAL NATURE	PACKAGING
WATER-BASED MUDS			
STABILITE® II	Asphalt shale inhibitor	Heavy hydrocarbons	22,7 kg bags
OPTITROL®	Low viscosity fluid loss control/total mud conditioner (up to 200C)	Resin polymer complex	20 kg bags (dry)/ 200 l drums (liquid)
BLACKTROL®	Liquid gilsonite	Liquid asphalt polyglycol dispersion with surfactants	200 l drums
KLSP® (KOLA-SUPERDEEP)	Hi-temp fluid loss control agent (220C)	Water soluble polymer resin based cellulose derivative	20 kg bags
SHALE-X®	Shale hydration suppressant/well stabilizer	Methylsiloxane	200 l drums
POLYTROL®	4 th generation liquid amine shale inhibitor	Polyetheramines	200 l drums
KLA-FREE®	Liquid polyamine shale inhibitor	Polyamines	200 l drums
POLYCAP®	Encapsulating agent	PHPA (partially hydrolyzed polyacrylamide)	22,7 kg bags
TERRAPAN®	Hi Temp Fluid loss control	Polyacrylate copolymer	22,7 kg bags
CLEAN-STAR®	Fluid loss control starch	Non Fermenting Pregelatinized Starch	22,7 kg bags
G-DRILL®	Polyglycol shale inhibitor	Polyglycols	200 l drums
OIL-BASED MUDS			
LIQUITROL®	Liquid polymeric OBM fluid loss control additive	Proprietary liquid polymeric blend	200 l drums
CLOTONEX®	OBM fluid loss control additive (organophilic lignite)	Amine treated lignite	22,7 kg bags
STABILITE® OBM	OBM fluid loss control additive (gilsonite/asphaltite)	Gilsonite/asphaltite	22,7 kg bags
WELLBOND®	Lost circulation resin	Two-component resin blend	200 l drums
ADVANTA®	Non-damaging fluid loss control for OBM	Polymer	22,7 kg bag/200 l drum