

# SUPERSLIDER® PLATINUM

## PREMIUM GRADE ESTER-BASED DRILLING LUBRICANT

### Product Data Sheet

---

#### Description

SUPERSLIDER® PLATINUM is an enhanced ester lubricant, designed to drastically and rapidly decrease coefficient of friction, torque and drag when drilling ERD wells and long horizontal sections. Effective at a very low concentration (starting from 0.5% by volume).

#### Applications/Functions

- used in challenging well profiles: highly deviated wells, ERD and long horizontal sections
- instantly and effectively reduces metal/metal and metal/rock friction, torque and drag

#### Advantages

- non-foaming, non-greasing, non-damaging
- effective in freshwater as well as mono- and divalent brines
- may be used at all bottom-hole temperatures

#### Recommended treatment

Recommended concentrations for SUPERSLIDER® PLATINUM lubricant range from 0,5–3% by volume. Appropriate concentrations depend on the particular conditions. It blends easily either through a conventional mud hopper or directly into the mud system. As a good standard practice it should be added over one circulation to enable homogenization.

#### Typical properties

Viscous brown liquid

#### Handling

Please refer to the MSDS for specific instructions

#### Packaging

SUPERSLIDER® PLATINUM is packaged in 200 liters (180 kg) drums



**KAOTO**